



## SPARC T4-1 SERVER

IDEAL FOR WEB INFRASTRUCTURE,  
APPLICATION DEVELOPMENT

### KEY FEATURES AND BENEFITS

- 5x single-thread performance increase accelerates application performance and improves scalability
- Integrated on-chip cryptographic acceleration provides high levels of security without sacrificing application performance.
- Runs Oracle Solaris 10 and 11 with guaranteed binary compatibility and support for legacy applications.
- Smart, simple, and eco friendly designs offer greater energy and space optimization, increasing asset utilization while reducing operating costs.
- Integrated on-chip cryptographic acceleration provides high levels of security without sacrificing application performance.
- Built-in, no-cost virtualization technology with Oracle VM Server for SPARC and Oracle Solaris Containers improves utilization and reduces operational overhead.

*Oracle's SPARC T4 servers running Oracle Solaris delivers world record performance on a highly scalable, secure and integrated platform optimized for enterprise software. With a 5x improvement in single-thread performance, SPARC T4 servers are highly optimized for Oracle and 3<sup>rd</sup> party software. The new SPARC T4-1 is a highly cost efficient platform for web infrastructure, middleware and application development.*



Figure 1: The SPARC T4-1 server offers maximum security, speed, and scale for your Web infrastructure.

### Product Overview

The SPARC T4-1 server is powered by the SPARC T4 processor that combines a new level of single-threaded performance along with high overall system throughput. The advanced SPARC T4 processor features integrated on-chip cryptographic support that provides wire speed encryption capabilities without an application performance penalty

The SPARC T4-1 is equipped with one SPARC T4 processor and 16 DIMM slots, which can support a total of 512 GB of memory when populated with 32 GB DIMMs. The SPARC T4-1 delivers highly expandable internal storage and network connectivity as the server has room for a combination of eight hard disk drives or solid state drives and six PCI Express card slots.

Also included are four 1GbE ports and up to two 10GbE XAUI ports. The SPARC T4-1 server comes integrated at no additional cost with Oracle VM Server for SPARC and Oracle Solaris. The SPARC T4-1 supports both Solaris 10 and Solaris 11 including the latest Oracle Solaris Containers, Oracle Solaris ZFS and Electronic Prognostics.

## SPARC T4-1 Server Specifications

Key Applications	
<ul style="list-style-type: none"> <li>• Web serving and web services</li> <li>• Application development, staging and testing</li> <li>• Middleware and security applications</li> <li>• Departmental and specialized application</li> <li>• Database and analytics</li> </ul>	
Architecture	
Processor	
<ul style="list-style-type: none"> <li>• Eight-core 2.85GHz SPARC T4 processor</li> <li>• One processor per system, maximum 64 threads</li> <li>• Eight floating-point units</li> <li>• New on-chip Encryption Instruction Accelerators with direct non-privileged support for 16 industry-standard cryptographic algorithms plus random number generation in each of the eight cores: AES, Camellia, CRC32c, DES, 3DES, DH, DSA, ECC, Kasumi, MD5, RSA, SHA-1, SHA-224, SHA-256, SHA-384, SHA-512</li> </ul>	
Main Memory	
<ul style="list-style-type: none"> <li>• 16 DDR3 DIMM slots, system maximum of 512 GB</li> <li>• Support for 4 GB, 8 GB, 16 GB and 32 GB DIMMs</li> </ul>	
System Architecture	
<ul style="list-style-type: none"> <li>• SPARC V9 architecture, ECC protected</li> </ul>	
Cache per Processor	
<ul style="list-style-type: none"> <li>• Shared L3, 4MB cache and eight cores with private L2 128K cache</li> </ul>	
Interfaces	
<ul style="list-style-type: none"> <li>• Network. 4x 1Gb (10/100/1000Mbps) integrated Ethernet ports.</li> <li>• Up to two optional option slots for 10GbE XAUI connections.</li> <li>• Expansion bus. Six total.</li> <li>• Ports. Four external USB 2.0 ports. One VGA port</li> </ul>	
Mass Storage	
<b>Internal disk:</b>	Up to eight 300 GB or 600 GB 10000 rpm 2.5-inch SAS HDD drives or 100GB or 300GB SSD drives Internal DVD: One slim line SATA DVD+/- RW
<b>External storage</b>	Oracle offers a complete line of best-in-class, innovative storage, hardware, and software solutions, along with renowned world-class service and support. For more information, please refer to <a href="http://oracle.com/storage">oracle.com/storage</a> .

Power	
<ul style="list-style-type: none"> <li>• Two hot-swappable AC 1200W redundant (N+1) power supplies</li> <li>• Maximum operating input current: 8.57A @ 100 V AC</li> <li>• Maximum operating input current: 4.2A @ 200 V AC</li> <li>• Maximum operating input power at 100 V AC: 771W</li> <li>• Maximum operating input power at 200 V AC: 762W</li> </ul>	
Key RAS Features	
<ul style="list-style-type: none"> <li>• Hot-pluggable disk drives</li> <li>• Redundant, hot-swappable power supplies and fans</li> </ul>	

<ul style="list-style-type: none"> <li>• Environmental monitoring</li> <li>• Extended ECC, error correction and parity checking memory</li> <li>• Easy component replacement</li> <li>• Integrated disk controller with RAID 0, 1 and 1E</li> <li>• Electronic Prognostics</li> </ul>
<b>Software</b>
<b>Operating System</b>
<ul style="list-style-type: none"> <li>• Oracle Solaris 11 or later</li> <li>• Oracle Solaris 10 8/11</li> <li>• Support for Solaris 10 9/10 and Solaris 10 10/09 + Oracle Solaris 10 8/11 Patch set</li> </ul>
<b>Software Included</b>
<ul style="list-style-type: none"> <li>• Oracle Solaris 11, including Oracle VM Server for SPARC</li> <li>• Electronic Prognostics</li> </ul>
<b>Virtualization</b>
<ul style="list-style-type: none"> <li>• Built-in, no-cost Oracle VM Server for SPARC and Oracle Solaris Containers provide the flexibility and power of 64 virtual systems in a single SPARC T4-1 server</li> </ul>
<b>Remote Management</b>
<ul style="list-style-type: none"> <li>• Oracle Integrated Lights Out Manager (ILOM)</li> <li>• One dedicated 10/100base-T Ethernet management port</li> <li>• In-band, out-of-band, and sideband network management access via any one of the four main Ethernet ports of the server</li> <li>• One RJ-45 serial management port</li> <li>• DTMF-style command-line interface</li> <li>• Support for access via SSH 2.0, HTTPS, RADIUS, LDAP, and Microsoft Active Directory</li> <li>• Browser-based GUI for control of the system through a graphical interface</li> <li>• IPMI 2.0, SNMP v1, v2c, and v3</li> <li>• Remote management with full keyboard, video, mouse, storage (KVMS) redirection and remote media capability (floppy, DVD, CD, and more)</li> <li>• Ability to monitor and report system and component status on all FRUs</li> </ul>
<b>Environment</b>
<b>Temperature</b>
<ul style="list-style-type: none"> <li>• Operating relative humidity: 10% to 90% RH, 27°C (80.6°F) maximum wet bulb (noncondensing); IEC 60068-2-56 Test Cb</li> <li>• Nonoperating relative humidity: 93% RH, 38°C (100.4°F) maximum wet bulb (noncondensing); IEC 60068-2-56 Test Cb</li> </ul>
<b>Altitude</b>
<ul style="list-style-type: none"> <li>• Operating altitude: 0 to 3,000 m (10,000 ft.); IEC 60068-2-13 Test M, and 60068-2-41 Test Z/BM</li> <li>• Nonoperating altitude: 0 to 12,000 m (40,000 ft.); IEC 60068-2-13 Test M</li> </ul>
<b>Acoustic Noise</b>
<ul style="list-style-type: none"> <li>• Operating/idling acoustic noise 7.1B (LwAD: 1 B = 10 dB) and 63dB operating max (LpAM: bystander positions)</li> </ul>
<b>Cooling</b>
<ul style="list-style-type: none"> <li>• 2317 Btu/hr, 145 cfm maximum</li> </ul>

### Regulations

**Safety:** UL/CSA-60950-1, EN60950-1, IEC60950-1 CB Scheme with all country deviations, IEC825-1, 2 CFR21 part 1040, CNS14336

**RFI/EMC:** EN55022 Class A, 47 CFR 15B Class A, ICES-003 Class A, VCCI Class A, AS/NZ3548 Class A, CNS 13438 Class A, KSC 5858 Class A, EN61000-3-2, EN61000-3-3

**Immunity:** EN55024, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11

**Regulatory:** CE, FCC, ICES-003, C-tick, VCCI, GOST-R, BSMI, MIC, UL/cUL, UL/Smarmk

**Ergonomics:** EK1-ITB-2000

**European Union Directives:** 2006/95/EC (73/23/EEC) Low Voltage Directive, 2004/108/EC (89/336/EEC) EMC Directive, 2002/96/EC Waste Electrical and Electronic Equipment (WEEE) Directive, 2002/95/EC Restriction of Hazardous Substances (RoHS) Directive

### Dimensions and Weight

**Height:** 88 mm (3.49 in); 2 RU

**Width:** 425 mm (16.75 in)

**Depth:** 714 mm (28.13 in)

**Weight:** Approximately 27.2 kg (60 lb.) max, without rackmount kit.

### Warranty

The SPARC T4-1 comes with a one-year warranty. Visit [oracle.com/us/support/policies/](http://oracle.com/us/support/policies/) for more information about Oracle's hardware warranty.

### Complete Support

With Oracle Premier Support, you'll get the services you need to maximize the return on your Oracle SPARC server investment—our complete system support includes 24/7 hardware service, expert technical support, proactive tools, and updates to Oracle Solaris, Oracle VM, and integrated software (such as firmware) – all for a single price. Learn more at [oracle.com/support](http://oracle.com/support).

### Contact Us

For more information about Oracle SPARC T4-1 server, visit [oracle.com](http://oracle.com) or call +1.800.ORACLE1 to speak to an Oracle representative.



Oracle is committed to developing practices and products that help protect the environment

Copyright © 2012, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark licensed through X/Open Company, Ltd. 0611

**Hardware and Software, Engineered to Work Together**